

## Portable UHF RFID Reader.

R-FLOW2 is a portable UHF Reader/writer with high performance capabilities, according to EPC Gen2 standard.

R-FLOW2 allow you to improve inventory process in a very fast and very efficiently way, up to 15m reading distance, and 700 tags/second.

R-FLOW2 saves the inventory files in an internal memory. Ready to download through USB Bluetooth, ethernet or wifi.

The reader implements a new functionality, allowing us trace any tag.

Supporting up to 4 antennas, R-FLOW2 is a perfect device for creating check points. Also it can be used hanging on a shoulder strap, installed in a forklift, robot or other vehicles.

### Key Features.

L-UHF EPC Gen2 Reader/writer

-Up to 4 external antennas

-Trace functionality

### Software included.

-API (Application programming interface)

-App android

### Ordering

R-FLOW2 KIT

### Included

Lector RFID UHF portátil de alto rendimiento

R-FLOW2-ANT1 Antena portátil de alto rendimiento

R-FLOW2-B2000 Batería 2.000 mAh (2 unidades)

R-FLOW2-CBD Cargador de baterías doble

R-FLOW2-MTR1 Maletín de transporte

### Optional accessories

R-FLOW2-ARM Wall mounting enclosure

### Technical data

Connectivity	Ethernet
	USB
	Bluetooth
	WiFi (2,4GHz)
Output Power	0 to 30dbm, step 0.5dBm, accuracy +/- 1dBm
Power Supply	Jack DC: 12/24 Vdc
	Battery
Power consumption	24Wmax, 10Wtyp
Antenna	1 External UHF antenna
	Up to 4 external antennas (Optional)
Transponder	EPC Class1 Gen2
	ISO 18000-6-C
Mechanical	Dimensions: 160x155x85mm
	Weight: 800gr (without battery)



Conócelo →

